



INTEGRAL WATERPELLER

WATER REPELLENT ADMIXTURE FOR CONCRETE AND MORTAR

DESCRIPTION

INTEGRAL WATERPELLER is a balanced blend of stearate water repellents and other chemicals which, when used as an admixture, forms an internal barrier against water penetration. INTEGRAL WATERPELLER also increases the plasticity of mortar, reduces water absorption and thereby guards against freeze-thaw damage. It is available in powdered form without chlorides or in a liquid formula which contains chlorides for additional densification and acceleration of the mortar or concrete. INTEGRAL WATERPELLER will not increase the air content of mortar or concrete.

PRIMARY APPLICATIONS

- Mass concrete
- Foundation walls
- Floors
- Cement stucco
- Mortar for setting masonry and glass block

FEATURES/BENEFITS

- Reduces moisture absorption as much as 60%
- Reduces capillary action
- Reduces vapor transmission through walls and slabs
- Provides greater workability
- Does not effect bond strength of mortar

TECHNICAL INFORMATION

Typical Engineering Data

Appearance

INTEGRAL WATERPELLER liquid has an amber color.

INTEGRAL WATERPELLER powder is a white powdery material.

Test Results	Absorption Ratio Fed. Spec. SS-C-181b	Relative Absorption	Concrete Absorption Total Immersion	
			10 minutes	24 Hours
Plain Mortar	.34	100%	1.28%	4.10%
Mortar with "Dry" Waterpeller	.18	53%	.47%	.65%
Mortar with "Liquid" Waterpeller	.16	47%	—	—

PACKAGING

INTEGRAL WATERPELLER LIQUID is packaged in 55 gal (208 L) drums and 5 gal (18.9 L) pails. INTEGRAL WATERPELLER POWDER is available in 25 lb (11.3 kg) bags.

SHELF LIFE

1 year in original, unopened package.

SPECIFICATIONS/COMPLIANCES

INTEGRAL WATERPELLER is approved for use by The Veterans Administration and by The City of Cleveland Board of Building Standards & Appeals.

DOSAGE RATES

1 to 1½ gal (3.9 to 5.7 L) liquid or 4 to 6 lb (1.8 to 2.7 kg) powder of INTEGRAL WATERPELLER will treat 1 yd³ (.76m³) of concrete or mortar.

DIRECTIONS FOR USE

Add INTEGRAL WATERPELLER to concrete or mortar in the following proportions:

Liquid: 1 qt (0.95 L) per 94 lb (42.7 kg) bag of cement

Powder: 1 lb (0.45 kg) per 94 lb (42.7 kg) bag of cement. 1/4 lb per bag of prepared mortar.

In cement-lime mortar the above quantities should be added for each 1 ft³ (0.03m³) of lime, in addition to the quantity added for each bag of cement. INTEGRAL WATERPELLER may be added to the mix after all other components have been added.

Note: The Euclid Chemical Company recommends the contractor follow typical cold weather concreting practices such as the guidelines in ACI 306, Standard Specification for Cold Weather Concreting.

CLEAN-UP

Clean tools and equipment with water before mortar hardens.

PRECAUTIONS/LIMITATIONS

- Liquid INTEGRAL WATERPELLER must be stored above 32°F (0°C).
- In all cases, consult the Safety Data Sheet before use.

Rev. 02.17

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.