



INCRETE ULTRA GRIP

SKID-RESISTANT ADDITIVE FOR SEALERS

PACKAGING

1 lb (0.45 kg) and 15 lb (6.8 kg) units

YIELD

1 cup (8 oz liquid measure (237 ml)
per gal (3.8 L) or 5 cups (1 lb (0.45 kg)
per 5 gal (18.9L) of sealer.

APPEARANCE

Dry white powder

CLEAN UP

Clean tools and equipment with
water before the material hardens.

SHELF LIFE

4 years in original,
unopened containers

BRIEF OVERVIEW

INCRETE ULTRA-GRIP is a colorless, finely-graded, polypropylene non-slip additive for solvent-based sealers and coatings. INCRETE ULTRA-GRIP will stay suspended in solution without continuous stirring. INCRETE ULTRA-GRIP has a larger particle size than most skid-resistant additives and can be used where slip hazards are more severe.

PRODUCT CHARACTERISTICS

ADVANTAGES

- Creates a slip-resistance surface
- Colorless
- Shape means better sealer wear than silica
- Large particle size for additional slip resistance

COMMON APPLICATION METHODS

- Stir into solvent-based sealer of choice

COMMON USES

- Interior/Exterior
- For use in most solvent-based sealers
- Exterior stamped concrete
- Integrally colored concrete
- Stained and other decorative concrete
- Pavers
- May be used in pigmented stain sealers

TECHNICAL INFORMATION

Composition: Polypropylene powder

Particle Size: 20 Mesh

Can be used to create a static coefficient of friction of 0.8 or greater. Results may vary depending on coating, substrate and application techniques.

DIRECTIONS FOR USE

INCRETE ULTRA-GRIP can be used in most solvent-based sealers and coatings where increased slip resistance is desired. INCRETE ULTRA-GRIP is especially effective over decorative concrete surfaces where other non-skid materials can not be used because of their color.

PROCEDURE

Mix sealer or coating to proper consistency. Slowly add the recommended amount of INCRETE ULTRA-GRIP and remix until properly dispersed. Apply sealer or coating as directed without over-rolling. If sealer is allowed to sit unused for a period of time, re-mix to assure INCRETE ULTRA-GRIP has not settled out.

PRECAUTIONS/LIMITATIONS

- INCRETE ULTRA-GRIP is designed for use in solvent-based sealers.
- INCRETE ULTRA-GRIP may not be fine enough to be used in some spray applications. Test for suitability.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 03.26

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.