



EUCLID CHEMICAL

FORMSHIELD PURE

**PREMIUM, OIL-BASED, CHEMICALLY REACTIVE, LOW VOC
CONCRETE FORM RELEASE**

DESCRIPTION

FORMSHIELD PURE is a premium, chemically reactive concrete form release agent with exceptional performance and ease of use that is unmatched by water-based form release products. **FORMSHIELD PURE** has a unique crystal clear formulation containing a proprietary ingredient that provides release capability superior to traditional form oils, making it ideal for use in precast and architectural concrete applications. **FORMSHIELD PURE** is environmentally friendly and compliant with all VOC regulations in the U.S. and Canada. Because it is not water-based, **FORMSHIELD PURE** does not require protection from freezing. Forms treated with **FORMSHIELD PURE** can be put to use faster than those treated with water-based release products. Metal, plastic, wood and composition forms strip cleanly with **FORMSHIELD PURE**.

PRIMARY APPLICATION

Preventing the adhesion of concrete to forms of all types in precast and architectural concrete applications

FEATURES/BENEFITS

- Forms release easily and cleanly from concrete
- No staining
- Compliant with all VOC regulations, including Federal EPA, OTC, LADCO, Maricopa County, CARB, and SCAQMD
- Dramatically reduces the occurrence of voids and bugholes
- Tolerant to freezing conditions during storage and transportation
- Treated forms are ready for use quickly
- DOT non-regulated: easy storage and shipping
- Very low odor

TECHNICAL INFORMATION

VOC content <5 g/L
Weight/gal..... 7.3 lb/gal (0.86 kg/L)
Appearance: Formshield PURE is a crystal clear liquid

PACKAGING

FORMSHIELD PURE is packaged in 275 gallon (1041 L) totes, 55 gal (208 L) drums and 5 gal (18.9 L) pails.

SHELF LIFE

2 years in original, unopened container

SPECIFICATIONS/COMPLIANCES

- Corp of Engineers CE 1401.01 (17.4) & CW 03101 (5.3)
- GSA CE 204 (3-03-K)
- ACI 347-68
- Compliant with Federal, OTC, California, and Maricopa County regulations

COVERAGE

	ft ² /gal (m ² /L)
Plywood Forms	350 to 500 (8.59 to 12.27)
Wood Composition Forms	350 to 500 (8.59 to 12.27)
Plastic Forms	800 to 1000 (19.63 to 24.54)
Metal Forms	800 to 1000 (19.63 to 24.54)

Note: Coverage rates are approximate and for estimating purposes only. Surface temperature, porosity and texture will determine actual material requirements.

MISCELLANEOUS

FORMSHIELD PURE

 MASTER FORMAT #:
03 11 00

DIRECTIONS FOR USE

Surface Preparation: The form surface must be free from dirt, cement paste, hardened concrete and other residue that could transfer to the finished concrete surface. Before coating plywood forms, apply a heavy brush coat to the plywood edges to protect laminations.

Application: In cold weather or if FORMSHIELD PURE has been stored in a cold location, gently stir the product before using. FORMSHIELD PURE can be applied by brush, spray or roller. Apply in a continuous film, avoiding excessive buildup, runs and puddles. Forms treated with FORMSHIELD PURE will be ready to use within one hour on plywood and 2 to 3 hours on metal and plastic forms. Used forms can be re-coated with FORMSHIELD PURE if proper surface preparation techniques are followed.

CLEAN-UP

Clean tools and application equipment immediately after use with mineral spirits. Clean drips and overspray while still wet.

PRECAUTIONS/LIMITATIONS

- Do not thin or dilute FORMSHIELD PURE.
- The viscosity of FORMSHIELD PURE increases at low temperatures, resulting in reduced sprayability.
- In all cases, consult the Safety Data Sheet before use.

Rev. 02.17

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.