



SAFETY DATA SHEET

1. Identification

Material name: WEATHER-GUARD
Material: 052A 55

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc.
2835 Grand-Allee
Saint Hubert QC J4T 2R4
CA

Contact person: EH&S Department
Telephone: (450)465-2233
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1B
Aspiration Hazard Category 1

Unknown toxicity - Health

Acute toxicity, oral 90.07 %
Acute toxicity, dermal 90.31 %
Acute toxicity, inhalation, vapor 99.9 %
Acute toxicity, inhalation, dust or mist 99.76 %

Environmental Hazards

Acute hazards to the aquatic environment Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment 94.87 %



Chronic hazards to the aquatic environment 100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.
Causes serious eye irritation.
May cause genetic defects.
May cause cancer.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. In case of fire: Use... to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

**Mixtures**

| Chemical Identity | CAS number | Content in percent (%)* |
|------------------------------------|------------|-------------------------|
| Stoddard solvent (Mineral Spirits) | 8052-41-3 | 50 - <100% |
| 1,2,4-Trimethylbenzene | 95-63-6 | 1 - <5% |
| Xylene | 1330-20-7 | 0.1 - <1% |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures**Description of necessary first-aid measures**

| | |
|--|---|
| Inhalation: | Move to fresh air. |
| Skin Contact: | Take off immediately all contaminated clothing. Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention. |
| Eye contact: | Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention. |
| Ingestion: | Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Personal Protection for First-aid Responders: | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.



Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation): Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Safe handling advice: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke.

Storage



Safe storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Type | Exposure Limit Values | Source |
|------------------------------------|---------|-----------------------|--|
| Stoddard solvent (Mineral Spirits) | TWA | 100 ppm | US. ACGIH Threshold Limit Values, as amended (2011) |
| | PEL | 500 ppm 2,900 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006) |
| 1,2,4-Trimethylbenzene | REL | 25 ppm 125 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010) |
| | TWA | 25 ppm 125 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989) |
| | TWA | 25 ppm 125 mg/m3 | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008) |
| | AN ESL | 25 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011) |
| | ST ESL | 140 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (02 2013) |
| | ST ESL | 700 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (02 2013) |
| | AN ESL | 125 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011) |
| | TWA PEL | 25 ppm 125 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010) |
| | TWA | 25 ppm | US. ACGIH Threshold Limit Values, as amended (2011) |
| Xylene | STEL | 150 ppm 655 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010) |
| | REL | 100 ppm 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010) |
| | STEL | 150 ppm 655 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010) |
| | REL | 100 ppm 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010) |
| | STEL | 150 ppm 655 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010) |
| | REL | 100 ppm 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010) |
| | STEL | 150 ppm 655 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989) |
| | TWA | 100 ppm 435 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989) |
| | TWA | 100 ppm 435 mg/m3 | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008) |
| | STEL | 150 ppm 655 mg/m3 | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008) |
| | ST ESL | 350 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011) |
| | ST ESL | 80 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011) |
| | AN ESL | 42 ppb | US. Texas. Effects Screening Levels (Texas |



| | | | |
|--|---------|-------------------|--|
| | | | Commission on Environmental Quality), as amended (07 2011) |
| | AN ESL | 180 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011) |
| | STEL | 150 ppm 655 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010) |
| | Ceiling | 300 ppm | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010) |
| | TWA PEL | 100 ppm 435 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010) |
| | TWA | 100 ppm | US. ACGIH Threshold Limit Values, as amended (2011) |
| | STEL | 150 ppm | US. ACGIH Threshold Limit Values, as amended (2011) |
| | PEL | 100 ppm 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006) |

| Chemical name | Type | Exposure Limit Values | Source |
|------------------------------------|------|-----------------------|---|
| Stoddard solvent (Mineral Spirits) | STEL | 580 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 290 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Stoddard solvent (Mineral Spirits) | TWA | 100 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010) |
| Stoddard solvent (Mineral Spirits) | TWA | 100 ppm 525 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm 123 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm 123 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017) |
| Xylene | TWA | 100 ppm 434 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009) |
| | STEL | 150 ppm 651 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009) |
| Xylene | TWA | 100 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | STEL | 150 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |



| | | | |
|--------|------|-------------------|---|
| Xylene | TWA | 100 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010) |
| | STEL | 150 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010) |
| Xylene | STEL | 150 ppm 651 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017) |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|--|-------------------------------|---------------------|
| Xylene (Methylhippuric acids: Sampling time: End of shift.) | 1.5 g/g (Creatinine in urine) | ACGIH BEI (03 2013) |

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke.

9. Physical and chemical properties**Appearance**

Physical state: liquid
Form: liquid
Color: Colorless
Odor: Mild petroleum/solvent
Odor threshold: No data available.
pH: No data available.



| | |
|--|---|
| Melting point/freezing point: | No data available. |
| Initial boiling point and boiling range: | 149 °C 300 °F |
| Flash Point: | 40 °C 104 °F(Tag closed cup) |
| Evaporation rate: | Slower than Ether |
| Flammability (solid, gas): | No |
| Upper/lower limit on flammability or explosive limits | |
| Flammability limit - upper (%): | 6 %(V) |
| Flammability limit - lower (%): | 0.70 %(V) |
| Explosive limit - upper: | No data available. |
| Explosive limit - lower: | No data available. |
| Vapor pressure: | 2 mmHg (20 °C 68 °F) |
| Vapor density: | Vapors are heavier than air and may travel along the floor and in the bottom of containers. |
| Relative density: | 0.787 |
| Solubility(ies) | |
| Solubility in water: | Practically Insoluble |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |
| Auto-ignition temperature: | No data available. |
| Decomposition temperature: | No data available. |
| Viscosity: | < 20.5 mm ² /s (40 °C 104 °F) |

10. Stability and reactivity

| | |
|--|--|
| Reactivity: | No data available. |
| Chemical Stability: | Material is stable under normal conditions. |
| Possibility of hazardous reactions: | No data available. |
| Conditions to avoid: | Heat, sparks, flames. |
| Incompatible Materials: | Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. |
| Hazardous Decomposition Products: | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

11. Toxicological information

Information on likely routes of exposure

| | |
|----------------------|---|
| Inhalation: | In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes. |
| Skin Contact: | Causes mild skin irritation. |
| Eye contact: | Causes serious eye irritation. |



Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 6,663.34 mg/kg

Dermal

Product: ATEmix: 6,816.03 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Rat): 10,200 mg/m³

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene in vivo (Rabbit): Irritating

Xylene in vivo (Rabbit): Moderate irritant

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene Rabbit, 30 min: Not irritating

Xylene Rabbit, 24 hrs: Moderately irritating

Respiratory or Skin Sensitization

Product: No data available.

**Carcinogenicity****Product:** May cause cancer.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity**In vitro****Product:** No data available.**In vivo****Product:** No data available.**Reproductive toxicity****Product:** No data available.**Specific Target Organ Toxicity - Single Exposure****Product:** No data available.**Specific Target Organ Toxicity - Repeated Exposure****Product:** No data available.**Aspiration Hazard****Product:** May be fatal if swallowed and enters airways.**Other effects:** No data available.**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**1,2,4-Trimethylbenzene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 7.19 - 8.28 mg/l
Mortality



Xylene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:**Fish**

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability**Biodegradation**

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential**Bioconcentration Factor (BCF)**

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Stoddard solvent (Mineral Spirits) Log Kow: 3.16 - 7.15

Xylene Log Kow: 3.12 - 3.20

Mobility in soil:

No data available.

Other adverse effects:

Harmful to aquatic organisms.

13. Disposal considerations**Disposal methods:**

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.



Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG III

CFR / DOT:

UN1866, Resin solution, 3, PG III

IMDG:

UN1866, RESIN SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | 100 lbs. |
| Methanol | 5000 lbs. |

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | 100 lbs. |
| Methanol | 5000 lbs. |



SARA 311/312 Hazardous Chemical

| <u>Chemical Identity</u> | <u>Threshold Planning Quantity</u> |
|------------------------------------|------------------------------------|
| Stoddard solvent (Mineral Spirits) | 10000 lbs |
| 1,2,4-Trimethylbenzene | 10000 lbs |
| Xylene | 10000 lbs |

SARA 313 (TRI Reporting)

| <u>Chemical Identity</u> |
|--------------------------|
| 1,2,4-Trimethylbenzene |

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | Reportable quantity: lbs. |

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

| <u>Chemical Identity</u> |
|------------------------------------|
| Stoddard solvent (Mineral Spirits) |
| 1,2,4-Trimethylbenzene |

US. Massachusetts RTK - Substance List

| <u>Chemical Identity</u> |
|------------------------------------|
| Stoddard solvent (Mineral Spirits) |
| 1,2,4-Trimethylbenzene |

US. Pennsylvania RTK - Hazardous Substances

| <u>Chemical Identity</u> |
|------------------------------------|
| Stoddard solvent (Mineral Spirits) |
| 1,2,4-Trimethylbenzene |

US. Rhode Island RTK

| <u>Chemical Identity</u> |
|--------------------------|
| 1,2,4-Trimethylbenzene |

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol



Not applicable

VOC:

Regulatory VOC (less water and exempt solvent) : 749 g/l

VOC Method 310 : 95.18 %

Inventory Status:

| | |
|--|--|
| Australia AICS: | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada DSL Inventory List: | All components in this product are listed on or exempt from the Inventory. |
| EINECS, ELINCS or NLP: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan (ENCS) List: | One or more components in this product are not listed on or exempt from the Inventory. |
| China Inv. Existing Chemical Substances: | One or more components in this product are not listed on or exempt from the Inventory. |
| Korea Existing Chemicals Inv. (KECI): | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada NDSL Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |
| Philippines PICCS: | One or more components in this product are not listed on or exempt from the Inventory. |
| US TSCA Inventory: | All components in this product are listed on or exempt from the Inventory. |
| New Zealand Inventory of Chemicals: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan ISHL Listing: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan Pharmacopoeia Listing: | One or more components in this product are not listed on or exempt from the Inventory. |



16. Other information, including date of preparation or last revision

Revision Date: 06/29/2020

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.