



# EUCON X20

## MID-RANGE WATER REDUCING ADMIXTURE

EUCLID CHEMICAL

MID-RANGE WATER REDUCERS

### DESCRIPTION

**EUCON X20** is a unique, mid-range water-reducing and plasticizing admixture manufactured with state of the art chemistries which provides exceptional slump retention without excessive retardation in very warm temperatures. EUCON X20 shows improved finishing characteristics when compared to other commonly used Type A or Type F water reducing admixtures. EUCON X20 contains no added chlorides and will not promote corrosion of steel.

### PRIMARY APPLICATIONS

- Flatwork concrete
- Architectural concrete
- General purpose ready mixed concrete
- Hot weather concreting

### FEATURES/BENEFITS

#### Plastic Concrete

- Improves finishability
- Improves workability
- Reduces water requirement
- Exceptional slump retention in hot weather

#### Hardened Concrete



- Increases all strength
- Reduces permeability
- Improves finished appearance
- Reduces shrinkage
- Increases durability
- Non-staining

### TECHNICAL INFORMATION

#### Performance Data

The following test results were achieved using typical ASTM C 494 mix design requirements, 517 lb/yd<sup>3</sup> (307 kg/m<sup>3</sup>) cement content and similar ( $\pm 0.5$ %) air content.

These results were obtained under laboratory conditions with materials and mix designs meeting the specifications of ASTM C 494. Changes in materials and mix designs can affect the dosage response of EUCON X20.



EUCON X20

MASTER FORMAT #:  
03 30 00 03 40 00  
03 70 00

## PACKAGING

EUCON X20 is packaged in bulk, 275 gal (1041 L) totes, 55 gal (208 L) drums, and 5 gal (18.9 L) pails.

## SHELF LIFE

1 year in original, unopened container.

## SPECIFICATIONS/COMPLIANCES

EUCON X20 meets or exceeds the requirements of:

- ASTM C 494, Type A and Type F
- AASHTO M 194

## DIRECTIONS FOR USE

EUCON X20 is typically used at dosages of 3 to 15 oz per 100 lbs (200 to 980 mL per 100 kg) of cementitious material. Dosage recommendations depend on the characteristics of the materials being used in the mix design. Higher dosages are acceptable with prior testing and confirmation of the desired performance with specific materials being used.

EUCON X20 should be added to the initial batch water when possible. It should not come in contact with dry cement or other admixtures until they are mixed with the concrete batch.

Field testing is strongly recommended to optimize dose range and performance expectations with local materials.

EUCON X20 is compatible with Euclid Chemical admixtures.

## PRECAUTIONS/LIMITATIONS

- Care should be taken to maintain EUCON X20 above freezing; however, freezing and subsequent thawing will not harm the material if thoroughly agitated. Never agitate with air or an air lance.
- Add to mix independent of other admixtures.
- In all cases, consult the Safety Data Sheet before use.

Rev. 11.14

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.